



DESCRIPTION		
OPTIC CHARACTERISTICS		
Powers:	+5.0 D to +34.0 D in 0.5 diopter increments	
Diameter:	6.0 mm	
Shape:	Biconvex, wavefront-designed anterior aspheric surface and ChromAlign™ technology to correct chromatic aberration for enhanced contrast sensitivity.	
Material:	Soft, foldable hydrophobic acrylic with UV and violet light absorber	
Refractive Index:	1.47 at 35° C	
Edge Design:	PROTEC frosted, continuous 360° posterior square edge	
ChromAlign™ Technology	Proprietary technology for chromatic aberration correction	
BIOMETRY*	CONTACT ULTRASOUND	OPTICAL
A-Constant:	118.8	119.3
AC Depth:	5.4 mm	5.7 mm
Surgeon Factor ¹ :	1.68 mm	1.96 mm
HAPTIC CHARACTERISTICS		
Overall Diameter:	13.0 mm	
Style:	C	
Design:	TRI-FIX , Haptics offset from optics, 1-piece lens	
RECOMMENDED INSERTION INSTRUMENTS		MODEL
The UNFOLDER ® Platinum 1 Series Screw-Style Inserter		DK7796
The UNFOLDER ® Platinum 1 Series Cartridge		1MTEC30

*Value theoretically derived for a typical 20.00 D lens. Johnson & Johnson Vision recommends that surgeons personalize their A-constant based on their surgical techniques and equipment, experience with the lens model and postoperative results.

Reference: 1. Holladay JT. International Intraocular Lens & Implant Registry 2003. *J Cataract Refract Surg.* 2003; 29:176-197. REF2016CT0151.

For healthcare professionals only.

Please read the Directions for Use for Important Safety Information and consult our specialists if you have any questions.

TECNIS, TECNIS Synergy, ProTEC, Tri-Fix and UNFOLDER are trademarks of Johnson & Johnson Surgical Vision, Inc.
©Johnson & Johnson Surgical Vision, Inc. 2019

PP2019OTH4216